

## HONEYTAK OPEN TOP CONTAINERS

Open top containers do not have a solid roof. A weather proof tarpaulin is used, that can be secured with ropes and cable sealing devices. Open tops are designed specially for over height (out of gauge) or bulky cargo. The open top allows cargo, such as machinery, to be loaded with a crane. They are also equipped with rings on the inside to secure cargo with straps for transit.

Honeytak can provide Original or Modified Open Top Containers

Following are some examples:

Features	Benefits
All corten construction and high grade paint system	Higher performance and lower maintenance
High strength top rails	Provide additional damage resistance and large top opening
All panels are 2.0t thick	Stronger and more impact resistant
Swinging/removal rear header	Allow full and unrestricted cargo access through the rear of the container
Standardized heavy duty tarpaulin	Full protection of cargo and lower maintenance costs
Stainless steel door holdback	Stronger than nylon door holdbacks. Minimize need for

replacement of lost or damaged door holdbacks

Double "Z" section bottom rails

Stronger than conventional "C" section bottom rails and eliminates maintenance of side floor rails

Standard size 19 ply hardwood floor

Unexposed floor center rail minimizes corrosion

boards with unexposed floor center rail

Crossmembers with extended top flange,  
extended rear sill top flange, open

Designed to minimize damages to floor and associated components and facilitate repairs

section tunnel bolster, unexposed floor

center rail

## SPECIFICATIONS FOR OPEN TOP CONTAINERS

<b>Ratings</b>	<b>(20ft)</b>	<b>(40ft)</b>
<b>Maximum Gross Weight</b>	30,480 kgs (67,200 lbs)	30,480 kgs (67,200 lbs)
<b>Tare Weight</b>	2,350 kgs (4,982 lbs)	3,950 kgs (8,774 lbs)
<b>Payload</b>	28,130 kgs (62,218 lbs)	26,530 kgs (58,426 lbs)
<b>External Dimensions</b>		
<b>Length</b>	6,058 mm (19'-10 1/2"+0/-1/4")	12,192 mm (40'-0"+0/-1/4")
<b>Width</b>	2,438 mm (8'-0"+0/-3/16")	2,438 mm (8'-0"+0/-3/16")
<b>Height</b>	2,591 mm (8'-6"+0/-3/16")	2,591 mm (8'-6"+0/-3/16")
<b>Internal Dimensions</b>		
<b>Length</b>	5,899 mm (19'-4 - 1/4")	12,024 mm (39'-5 3/8")
<b>Top Aperture Length</b>	5,787 mm (18'-11 - 13/16")	11,809 mm (38'-8 15/16")
<b>Width</b>	2,352 mm (7'-8 - 19/32")	2,350 mm (7'-8 9/16")
<b>Top Aperture Width</b>	2,250 mm (7'-4 - 5/8")	2,230 mm (7'-3 7/8")
<b>Height</b>	2,351 mm (7'-8 - 1/2")	2,351 mm (7'-8 1/2")
<b>Door Opening</b>		
<b>Width</b>	2,340 mm (7'-8-1/8")	2,338 mm (7'-8")
<b>Height</b>	2,295 mm (7'-5-7/8")	2,279 mm (7'-5 3/4")
<b>Cube</b>		
<b>Cubic Capacity</b>	32.2m3 (1,137 ft3)	67.0 m3 (2,366 ft3)
<b>Test Loads</b>		
<b>Stacking</b>	97,200 kgs (214,290 lbs)	97,200 kgs (214,290 lbs)
<b>Transverse Racking</b>	15,240 kgs (33,600 lbs)	15,240 kgs (33,600 lbs)
<b>Longitudinal Racking</b>	7,620 kgs (16,800 lbs)	7,620 kgs (16,800 lbs)
<b>Floor Strength</b>	7,260 kgs (16,000 lbs)	7,260 kgs (16,000 lbs)